

TYPE 23 RELAY DATA SHEET (CONTACT ACTION AND VOLTAGE ORDER)

| Contact Action ORDER | Minimum operating voltage volts (voltage order) | PO CODE | | Nominal Coil resistance Ω | Minimum limit cct op current mA | Saturation current mA |
|-------------------------|---|--------------|---------------------|-------------------------------------|------------------------------------|--------------------------|
| | | Wire-in code | Printed wiring code | | | |
| 2C | 4.4 | | 23/28PW | 58 | 58 | 105.0 |
| 2C | 5.9 | 23/25 | 23/25PW | 110 | 41 | 74.0 |
| 2C | 8.5 | 23/12 | 23/12PW | 220 | 29.7 | 54.0 |
| 2C | 10.0 | 23/18 | 23/18PW | 325 | 24.7 | 45.0 |
| 2C | 14.0 | 23/9 | 23/9PW | 530 | 19 | 35.0 |
| 2C | 18.0 | 23/7 | 23/7PW | 890 | 15.1 | 27.4 |
| 2C | 28.0 | 23/20 | 23/20PW | 2200 | 9.8 | 17.9 |
| 2C | 34 | 23/1 | 23/1PW | 3300 | 7.9 | 14.3 |
| 2C | 55.0 | 23/22 | 23/22PW | 7600 | 5.3 | 9.7 |
| 2K | 9.2 | | 23/30PW | 220 | 32 | 54.0 |
| 2K | 19.0 | 23/11 | 23/11PW | 890 | 16.4 | 27.4 |
| 2K | 37 | 23/23 | 23/23PW | 3300 | 8.6 | 14.3 |
| 4C | 10.4 | 23/19 | 23/19PW | 150 | 53 | 81.0 |
| 4C | 13.0 | | 23/24PW | 220 | 45 | 68.0 |
| 4C | 20.0 | 23/10 | 23/10PW | 530 | 28.5 | 43.0 |
| 4C | 27 | 23/4 | 23/4PW | 890 | 22.6 | 34.0 |
| 4C | 37 | 23/2 | 23/2PW | 1800 | 15.7 | 23.8 |
| 4C | 42.0 | 23/16 | 23/16PW | 2200 | 14.7 | 22.3 |
| 2C 2K | 4.6 | 23/13 | | 28 | 126 | 185.0 |
| 2C 2K | 10.8 | 23/8 | 23/8PW | 150 | 55 | 81.0 |
| 2C 2K | 13.2 | 23/26 | 23/26PW | 220 | 46 | 67.8 |
| 2C 2K | 38 | 23/6 | 23/6PW | 1800 | 16.2 | 23.8 |
| 2C 2K | 44.0 | 23/21 | 23/21PW | 2200 | 15.2 | 22.3 |
| 6M | 9.8 | | 23/29PW | 150 | 50 | 81.0 |
| 6M | 12.0 | | 23/27PW | 220 | 42 | 68.0 |
| 6M | 19.0 | 23/17 | 23/17PW | 530 | 26.7 | 43.0 |
| 6M | 25 | 23/5 | 23/5PW | 890 | 21.2 | 34.0 |
| 6M | 35 | 23/3 | 23/3PW | 1800 | 14.8 | 23.8 |
| 6M | 40.0 | 23/14 | | 2200 | 13.8 | 22.3 |
| 6B | 45 | 23/15 | | 2200 | 15.6 | 22.3 |